

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 February 2001 (01.02.2001)


PCT

(10) International Publication Number
WO 01/07733 A1

- (51) International Patent Classification⁷: E04H 17/00 (74) Agent: BARNARD, Eric, Edward; Brookes & Martin, High Holborn House, 52/54 High Holborn, London WC1V 6SE (GB).
- (21) International Application Number: PCT/GB99/02435
- (22) International Filing Date: 26 July 1999 (26.07.1999) (81) Designated States (*national*): AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicants and
(72) Inventors: MOSS, Frederick, James [GB/GB]; Tree-tops, 12 Oak Way, Studham, Bedfordshire LU6 2PE (GB). HOLLAND, Janusz, Lucien [GB/GB]; 111 Summerfield Crescent, Edgbaston, Birmingham B16 0EN (GB). HUGHES, Mark, Christopher [GB/GB]; 60 Monmouth Road, Warley Wood, Birmingham B67 5EE (GB).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ANTI-SCALING DEVICE



(57) Abstract: An anti-scaling device comprises a hollow central body (1) for mounting on a bar and several spike units (5) extending outwardly from the body (1) in different directions. Pairs of spike units (5) are rotatably and preferably detachably mounted on opposite sides of the central body (1). The device may further comprise serrated webs (7) extending outwardly from the central body (1) between the spike units (5). The device may also comprise rows of sharp-edged teeth (15) axially aligned along the central body (1). In an alternative embodiment the spike units (5) are in the form of partially rotatable serrated propellers (37). In another embodiment the spike units (5) are pivotably rotatably mounted. Preferably the device is moulded from plastics material.

WO 01/07733 A1



Published:

- With international search report.
- With amended claims.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.